

FRENCH BARREL	
WOOD	French oak (<i>Quercus petraea</i>)
ORIGIN	Selection of wood from central France
GRAIN	Extra-fine grain
CUT	Split stave
DRYING	Natural, open-air Tannin-Moisture Balance
CAPACITY	225 +/- 5 Litros
BENDING	"water bending" or "Traditional"
NO. OF STAVES	(28 - 32) parts
LENGTH	95 +/- 1 cm
THICKNESS	22 mm
BASES	6/8 parts. Optional toasting
HEAD DIAMETER	57 +/- 0,5 cm
BILGE DIAMETER	68 +/- 0,5 cm
BUNGHOLE (silicone plug)	<ul style="list-style-type: none"> · Truncated cone. Burning (Optional) · Standard : 45 +/- 1 mm / Optional: 50 +/-1 mm · Cylindrical (Optional)
WEIGHT	45 Kg
METALWORK (hoops)	6-8 bands of special galvanised steel
OPTIONAL	Bung
CONTROL	Seal check, identification of the barrel, final verification.
FINISH	<ul style="list-style-type: none"> · Fine sanding. Marking of Quercus "logo". · Type of wood and year of manufacture. · Wrapped in plastic film.

TOASTED TRH Tostado Rotativo Horizontal (Horizontal Rotating Toasting)
• 50 toasting profiles
 Consult our Technical Department (+34) 945 627 363

TRADITIONAL TOASTING Braziers fed by oak chippings. Time and temperature control.
• LIGHT (T.L.), MEDIUM (T.M.), MEDIUM Plus (T.M.+), STRONG (T.F.), QUERCUS
 Consult our Technical Department (+34) 945 627 363

One-year guarantee against any leakage and/or broken staves.